



GENERAL INFORMATION

Kameleon® Pearls are unique color changing pigments available in 2 dazzling colors. They are supplied in a dry form that may be added to S2-00 Transnebulae, House of Kolor brand clears.



SUBSTRATE

- KD3000 Series DTS Foundation Surfacer / Sealer
- SS01 Silver Sealer (Tinted with Kandy Koncentrates)
- Shimrin2® Base Coats



COMPONENTS

ITEM NUMBER	DESCRIPTION	SIZE
KPF103	Saphire (Limited Color Change)	90 Micron
KPF104	Aquarius	90 Micron

RU Series Reducers

- RU310 – Fast Reducer 65°F to 75°F
- RU311 – Medium Reducer 75°F to 85°F
- RU312 – Slow Reducer 85°F to 95°F
- RU313 – Very Slow Reducer 95°F to 100+°F
- RU300 - LV Cool Weather Reducer 70°F to 85°F
- RU301 - LV Warm Weather Reducer 85 to 100+°F



GUN SET UP

Refer to spray gun manufacturer's recommendations



MIXING RATIO

KARRIER BASECOAT COLOR	S2-00 & KPF OVER LIGHT BASE COLOR	DARK BASE COLOR
up to 3 : 1	up to 48 : 2	View online for V formal

Note: After Mixed together reduce 2 : 1



APPLICATION

Strain the paint into the paint gun. Apply 3 medium (almost wet) coats with 75% pattern overlap. Gun distance while spraying should be 4-6 inches. Walk long objects. Allow flash time between coats. Avoid dry spraying, as loss of adhesion is possible with pearls. Be sure that your spray equipment and environment are very clean and the spray pattern correct. An uneven spray gun pattern will make proper application impossible. Apply enough coats to achieve the effect you desire. Then begin clear coats.

NOTE: ANY KANDY OR ARTWORK APPLIED OVER KAMELEON® PEARLS CAN REDUCE OR COMPLETELY ELIMINATE THE COLOR CHANGE EFFECT. ALWAYS TEST ANY ARTWORK OR KANDY PLANNED ON A TEST PANEL.



DRY TIME

Allow to flash from 10 - 15 minutes between coats.
Let a Minimum of 20 - 30 minutes before Klear Coat application.



CLEAN UP

Clean equipment thoroughly with lacquer thinner or urethane reducer (check local regulations).

HEALTH AND SAFETY

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

IMPORTANT The contents of this package have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

If used as instructed, this product is designed to comply with VOC standards in low-VOC jurisdictions. Confirm compliance with state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.